



LaserBoxx

Single Frequency Lasers



Raman Spectroscopy
Brillouin Scattering
Interferometry
Dynamic Light Scattering
Holography
Laser Doppler Velocimetry
Shearography

LaserBoxx

One platform for all colors

The single frequency lasers from Oxxius have been designed with versatility in mind. They utilize advanced technologies such as DPSS lasers and stabilized laser diode.

Technology

DPSS lasers

The LCX and LPX *LaserBoxx* are diode-pumped solid-state (DPSS) laser sources. The unique feature of these models is a proprietary, **Alignement-free Monolithic Resonator (AMR)**.



The elements of the resonator are assembled into a single ultra-low-loss optical subsystem, using a proprietary crystal bonding technique.

Benefits of the AMR

This technology yields to highly efficient pump schemes and allows for the highest spectral quality and wavelength stability ($\leq 1\text{pm}$) on the market, as well as an important robustness over time. The LCX and LPX models are insensitive to temperature variations and to mechanical vibrations.



Diode lasers

The LBX and LSX models are based on integrating a **temperature-stabilized laser diode**.

Benefits of VBG stabilized lasers

These models deliver an ultra-narrow linewidth emission due to their stable design and their proprietary wavelength-locking routine.

Common key features

- Single frequency
- Narrow linewidth
- Up to 500 mW continuous wave
- Integrated control electronics
- Low profile laser head
- SM/PM/MM fiber coupling options
- USB and RS-232 interfaces
- 100 x 40 mm² Industry standard footprint (LBX and LCX)


Common specifications

- Power stability (over 8 h and $\pm 3\text{ K}$) $\pm 1\%$
- Power adjustment optional with L1C-MPA/AOM
- Optical noise (10 Hz - 20 MHz bandwidth) $\leq 0.2\%$, 2 m

Performances


Beam profile

LBX-633



Narrow linewidth spectrum

LSX-785S-ISO



Optical specifications

DPSS lasers


	Emission wavelength (Tolerance)	Optical power (Continuous wave)	Wavelength stability over 8 h and ± 3 K	Linewidth	Side mode suppression ratio	Polarization state	Beam waist diameter (at $1/e^2$)	Beam quality factor (M^2)	Beam circularity in far field	Coupling efficiency Into a single mode fiber				
LCX-532S	532.3 nm (± 0.5 nm)	50 / 100 / 150 200 / 300 mW	≤ 1 pm	≤ 1 MHz	≥ 30 dB	linear, vertical 100:1 extinction ratio	0.7 mm (± 0.1 mm)	≤ 1.1	$\geq 90\%$	$\geq 70\%$				
LPX-532S		500 mW												
LCX-553S	553.0 nm (± 0.4 nm)	50 / 100 200 mW												
LCX-561S	561.4 nm (± 0.4 nm)	50 / 100 150 / 200 mW												
LPX-561S		300 mW												
LCX-946S	946.0 nm (± 0.3 nm)	50 mW				linear, vertical 300:1 extinction ratio								
LCX-1064S	1064.6 nm ⁽¹⁾ (± 0.6 nm)	100 / 200 / 300 500 mW												

⁽¹⁾ The LCX-1064S also emits a class 1 visible aiming beam.


Diode lasers

	Emission wavelength (Tolerance)	Optical power (Continuous wave)	Wavelength stability over 8 h and ± 3 K	Linewidth	Side mode suppression ratio	Linear polarization extinction ratio	Beam waist diameter (at $1/e^2$)	Beam quality factor (M^2)	Beam circularity in far field	Coupling efficiency into a single mode fiber
LBX-633S	633 nm (± 0.5 nm)	40 mW	≤ 10 pm	≤ 100 MHz	≥ 35 dB	50:1	0.2 to 0.6 mm	≤ 1.9	$\geq 65\%$	$\geq 50\%$
LSX-785S-ISO	785 nm (± 0.5 nm)	150 mW with isolator			≥ 25 dB	100:1	0.4 to 0.6 mm	≤ 1.25	$\geq 90\%$	
LBX-830S	830 nm (± 0.5 nm)	150 mW			≥ 35 dB	50:1	0.5 to 1.0 mm	≤ 1.9	$\geq 65\%$	
LBX-785S-MM	785 nm (± 0.5 nm)	450 / 600 mW	≤ 10 pm	100 pm 60 pm typ.	≥ 35 dB	Delivery on a multimode fiber 100 μ m-core diameter 0.22 numerical aperture				
LBX-830S-MM	830 nm (± 0.5 nm)									
LBX-976S-MM	976 nm (± 0.5 nm)									
LBX-1064S-MM	1064 nm (± 0.5 nm)									


Power stability versus temperature
LCX-561S



Wavelength stability versus time
LCX-561S



Narrow linewidth spectrum
LCX-532S



L1C

The L1C platform offers an efficient, compact and cost-effective solution to add advanced features to the **LaserBoxx** lasers:

Motorized Power Attenuator (MPA)

Power adjustment; the MPA is a continuous control of the optical power. It is ideal to ensure wavelength stability.

- 0-100 % power range (full contrast with e-m shutter)
- Analog voltage or software command inputs
- Transmission ratio : $\geq 85\%$
- Response time: < 1 s
- Dynamic range ≥ 30 dB
- Digital modulation up to 5Hz with e-m shutter
- Compatible with an isolator

Acousto-Optic Modulator (AOM)

Modulated output; analog or digital modulation up to 3 MHz.

- Transmission ratio: $\geq 85\%$
- Response time: 100 ns typical
- Dynamic range ≥ 40 dB
- Electro-mechanical shutter for a complete extinction
- Plug & play version with BTC-AOM driver
- USB and Ethernet interfaces

Isolator (ISO)

An optical isolator protects the laser source in reflective environments.

- Degree of isolation ≥ 20 dB typ.
- Transmission ratio $\geq 70\%$ typ. (wavelength-dependent)
- Compatible with the MPA



L1C-532S

Fiber coupling

A rugged and compact accessory that injects the laser beam into a single mode (SM) fiber, a polarization maintaining (PM) fiber, or a multimode (MM) fiber.



Fiber coupling


	SM and PM Fiber	MM Fiber (50 μ m, 0.22 NA)
Coupling efficiency	LCX LPX LSX $\geq 70\%$ LBX-S $\geq 50\%$	$\geq 80\%$
Power stability over 8 h, ± 1.5 K	$\pm 2\%$	$\pm 2\%$
Polarization extinction ratio (PMF only)	$\geq 50:1$	n/a
Available optical connectors	FC-APC	AR-coated SMA FC-APC
Fiber length	2.0 m	2.0 m

System specifications


Plug and Play, CDRH-compliant versions

Dimensions in mm

LCX series
DPSS laser




LPX series
DPSS laser




The electro-mechanical shutter is standard on LPX models

LBX series
Stabilized laser diode



Optional heatsink available

LSX series
Stabilized laser diode



Optional heatsink available


Power-adjustable versions (PPA)

PPA - ControlBoxx




Fixed power versions (PPF)

PPF - RemoteBoxx



For improved stability

Heat sink




Compliance	CE and FDA 21 CFR 1040.10 / 1040.11
Operating temperature	10 to 38 °C (ambient air)
Power consumption	≤ 25 W
Storage temperature	0 to 60 °C

Supply voltage	100 to 240 VAC external power supply
Warm-up time	LCX, LPX: ≤ 10 minutes LBX, LSX: ≤ 2 minutes
Communication interfaces	USB, RS-232, dedicated interface


OEM - dedicated versions

Control electronics is integrated into the laser head

LCX series
DPSS Laser




LPX series
DPSS Laser




The electro-mechanical shutter is standard on LPX

LBX series
Stabilized laser diode



LSX series
Stabilized laser diode
Integrated isolator



	LCX and LPX	LBX and LSX
Compliance	FDA 21 CFR 1040.10 / 1040.11	
Operating temperature baseplate	10 to 50 °C	20 to 35 °C
Power consumption	≤ 25 W	≤ 10 W
Storage temperature	0 to 60 °C	
Supply voltage	5 to 12 VDC	
Warm-up time	≤ 10 minutes	≤ 2 minutes
Communication interfaces	USB, RS-232, dedicated electronical interface	





Our distributors

AUSTRALIA

Lastek Pty Ltd
Thebarton campus, University of Adelaide
10 Reid Street Thebarton SA 5031
Phone: (+61) 8 8443 8668
E-mail: jessica@lastek.com.au
Web: www.lastek.com.au

BRAZIL

Setup Instruments4Labs
Rua Acadêmico Hélio Ramos, 60, Várzea,
Recife-PE 50.740-533
Phone: (+55) (81) 3183-4342
Web: www.lsetup4labs.com.br/lp/analiseoptica

CHINA

Aunion Tech Co., Ltd
Room 905, F building, Everbright
convention and exhibition centre,
No. 86 CaoBao road, ShangHai 200235
Phone: (+86) 21 5108 3793
E-mail: info@auniontech.com
Web: www.auniontech.com

GERMANY

Mountain Photonics GmbH
Albert-Einstein-Str. 18
D-86899 Landsberg am Lech
Phone: (+49) (0) 8191 985199 0
E-mail: info@mountainphotonics.de
Web: www.mountainphotonics.de

INDIA

Specialise Instruments
1201, DS Business Galleria,
L.B.S Road, Kanjurmarg (W),
Mumbai-400078, Maharashtra
Phone: (+91) 022-68551200
Email : info@simc.co.in
Web: <https://simc.co.in>

ISRAEL

Rosh Electroptics
P.O.B 2667 Netanya 4212601
Phone: (+972) (0)9-8627401
E-mail: info@roshelop.co.il
Web: www.roshelop.co.il

ITALY

OPTOPRIM s.r.l
-Via Rota, 37,20900 Monza (MB)
Phone: (+39) 039 834977
- Via Monte Giberto, 15, 00138 Roma
Phone: (+39) 06 87657838
E-mail: info@optoprim.it
Web: www.optoprim.it

JAPAN

Autex
Shinjuku Takasago Bldg.
4F, 16-5 Tomihisa-Cho,
Shinjuku-Ku, Tokyo 162-0067
Phone: (+81) 3 322 66321
E-mail: sales32@autex-inc.co.jp
Web: www.autex-inc.co.jp

KOREA

L2K Co., Ltd.
A-305, 289-1 Daehwa-dong
Daedeok-gu Daejeon 306-754
Phone: (+82) 42 670 7744
E-mail: sales@l2k.kr
Web: www.l2k.kr

SPAIN & PORTUGAL

IberOptics Sistemas Ópticos, S.L
C/ Camino de Hormigueras, 124-4, 3º I
E-28031 Madrid
Phone: (+34) 91 3854 395
E-mail: info@iberoptics.com
Web: www.iberoptics.com

SINGAPORE

Acexon Technologies Pte Ltd
21 Bukit Batok Crescent
#20-83 WCEGA Tower, Singapore
Phone: 65-65657300
E-mail: sales@acexon.com
Web: www.acexontech.com

TAIWAN

Bio Accord
No. 142-2 Jiu-Kwang Rd
Panchiao, Taipei county (220)
Phone: (+886) 2 2250 5019
E-mail: biotal@ms37.hinet.net
Web: www.bioaccord.com.tw

UNITED KINGDOM

Photonic Solutions Ltd
Unit 2.2 Quantum Court
Heriot-Watt University Research Park
Edinburgh, EH14 4AP
Phone: (+44) (0)131 664 8122
E-mail: sales@photronicsolutions.co.uk
Web: www.photronicsolutions.co.uk

USA

RPMC Lasers, Inc.
203 Joseph Street
O'Fallon, MO-63366
Phone: (636) 272 7227
E-mail: rpmc@rpmclasers.com
Web: www.rpmclasers.com

VIETNAM

Atek Vietnam Co., Ltd
6th Floor, Viet Asia Building,
9 Duy Tan Street,
Dich Vong Hau Ward,
Cau Giay District, Hanoi City
Phone : (+84) 4.2120.3666
E-mail : thanh.nt@atekvietnam.com
Web : www.atekvietnam.com



OXXIUS SA
4 rue Louis de Broglie - 22300, Lannion, France
Phone: +33 296 48 70 28
E-mail: sales@oxxius.com
www.oxxius.com

